



## INSTALLATION INSTRUCTIONS

Tech Support  
856-768-5700 EXT 2  
TechSupport@LEDGlow.com

### LEDGLOW ADVANCED 7 COLOR FLEXIBLE MOTORCYCLE LIGHT KIT

1. **Prior to Installation:** Upon receiving your new light kit, we ask that you please test the kit first by temporarily connecting the red power wire to a 12 volt source and the black ground wire to an unpainted / exposed metal engine ground. Once the wires are temporarily secure, power on the kit to ensure full functionality before installing. If everything appears to be working correctly, power down the kit and prepare for installation.
2. **Installation:** Begin by first laying out the LED light strips similar to the way they will be installed. Make sure that the wires will be able to be routed in such a way that they will not be pinched, cut or exposed to heat. Also, keep the wires and strips away from all moving parts that may come in contact with either part of the kit. The control box is **not** waterproof, so it must be mounted in a dry, accessible location.
3. Once the strips and wires are mapped out, clean the proposed mounting surface with an alcohol prep pad or equivalent. Once clean, prep the surface with a 3M adhesion promoter. This promoter is a type of primer that combines with the glue on the 3M tape for a secure mounting on your surface. If the adhesion promoter is not used there is a chance that the tape could let go over time. Also, the mounting surface should be between 45 and 85 degrees Fahrenheit to achieve the strongest bonding results from the double sided adhesive. (Note: The surface area must be free of all oils, moisture, dirt and wax in order for the supplied adhesive tape to bond and adhere to the installation surface correctly.)
4. Next, temporarily place the lighting strips in the intended mounting position and loosely route the wires to the planned control box mounting area. Use the supplied zip ties to secure the wires to their mounting points.
5. Once the wires are secured and the mounting surface is double checked to be clean and dry, secure each strip by using the supplied double sided adhesive tape. Use the supplied wire ties at each end of the strip to act as a secondary anchor and mounting point for each. The wire ties are a very important step and should not be skipped. The wire ties will help ensure that the lighting strips stay adhered and in place during vehicle use and through seasonal temperature changes. Once this step is complete and the lighting strips are secure, allow ample time for the adhesive to settle and cure.
6. Route the red power wire from the control box to a positive (+) 12 volt source and the black ground wire to a well known ground (-) location. The white wire is for the antenna signal wire for the wireless remote. **(DO NOT CONNECT THIS TO ANYTHING)** If the wires need to be extended, use automotive grade, 16-18 GA wire for the red and black power wires only. Connect and secure the power supply lines only after everything is properly installed and mounted. If you do not follow this step it is very easy to blow the inline fuse on the red power wire.
7. The kit was designed using a modular locking plug system for connecting the LED lighting strips to the control box and vice versa. The wires are not to be cut, in an attempt to shorten or lengthen them. **If the wires or connectors of the kit are found to be cut or modified in any way, the manufacturer warranty is null and void. ANY alteration of the control box, lighting strips or wires may impact kit functionality and voids any warranties expressed or implied.**
8. **Controls:** This kit provides 7 solid colors options with multiple pattern abilities as well as several brightness levels which are easily operated using the included wireless remote. The remote includes four buttons, "A, B, C, D":

Button A: • Cycles through 7 solid colors as well as a color cycle and a color fade pattern.  
• Hold for 5 seconds to select brightness level when on a solid color.

Button B: • Activates strobing pattern when a single color is selected.  
• Hold to increase pattern speed when on color cycle/color fade pattern.



**Tech Support**  
**856-768-5700 EXT 2**  
**TechSupport@LEDGlow.com**

- Button C: • Activates fading pattern when a single color is selected.  
• Hold to decrease pattern speed when on color cycle/color fade pattern.

Button D: • Power On/Off

9. Once everything is connected, test the kit to ensure everything is working properly.

## Troubleshooting

If for some reason the kit or lights do not appear to operate, first check the installed inline mini fuse.

If the fuse is blown, check the wires on the entire kit to make sure that they are not cut, pinched or scorched. Fix any problem with the wiring and replace the fuse. If there is no damage to any of the wires and no water damage is visible to the control box, replace the fuse and test the kit again.

If the fuse is intact, clean the battery terminals and / or the both positive and negative wire connection points. Corrosion at the battery terminal can cause a poor connection or simulate being disconnected.

---

### *Limited Warranty and Disclaimer*

All LEDGlow Lighting, LLC. products come with a one year limited warranty on the internal parts of the product. This warranty starts from the date of purchase. LEDGlow Lighting, LLC. will replace or repair any qualifying defective product received by the company before the end of the warranty period. Installation of this product must be performed by a licensed professional. Should the failure of the product be the result of damage occurring as a result of improper installation, alteration of the product or an act or omission on the part of the consumer, this warranty is void. LEDGlow Lighting, LLC. shall not be responsible for any consequential damages which arise from the use and/or installation of the product. If the kit is installed in any manner other than specified, LEDGlow Lighting, LLC. reserves the right to deny any warranty claims at the discretion of the technical support department. The one year warranty is not transferable and is valid for up to one year from the original date of purchase. Any product return must include the original packaging, a statement of the alleged defect and an RMA number must be provided. All RMA numbers are valid for 14 days from issued date. Upon receipt of the returned product, the company will test the product for defect. If the results of the testing do not support the warranty claim, do not reveal any defect or indicate consumer negligence in the installation and handling of the product, then the product will be returned to you and you will be charged a reshipping fee. If the product is returned from an address within the continental United States, within the first 14 days after purchase, and is found to be defective, LEDGlow Lighting, LLC. will cover the cost of the return shipping with an emailed return label. This offer is only valid for the continental US. All international shipping, customs fees and/or duty charges are solely the responsibility of the consumer.

### *Additional Disclaimer Terms*

Lights are for off road use only; please check your local and state laws for the proper use of this product.

- Improper installation of electricity-using products such as lighting may cause damage to any vehicle or device to which the improperly handled or installed lighting is attached.
- Improperly installed product may cause electrical injury to persons.
- It is recommended that the kit be installed by a licensed professional.
- LEDGlow Lighting, LLC. assumes no liability for the installation of the product.
- Warranty or liability will not exceed the product purchase price which shall be the buyer's sole and exclusive remedy.

THERE ARE NO WARRANTIES WHICH EXTEND BEYOND THE WARRANTIES DESCRIBED ON THE FACE HEREOF INCLUDING ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. (LEDGlow Lighting, LLC. AT ITS DISCRETION, MAY PROVIDE REMEDY OF RETURN OF PURCHASE PRICE OR REPAIR OR REPLACEMENT OF DEFECTIVE PRODUCT AS BUYERS SOLE AND EXCLUSIVE REMEDY.)

LEDGlow Lighting, LLC.  
150 Cooper Road - Suite A-2 West Berlin, NJ 08091